

### **AMENDMENTS TO THE CLAIMS**

This listing of the claims will replace all prior versions, and listings, of the claims in this application.

#### **Listing of claims:**

1. (previously presented) An optical branching component having an operational wavelength region, comprising two optical waveguides coupled between two optical couplers, wherein there is an effective optical path length difference between the two waveguides, and wherein each said optical coupler comprises a multi-mode interference (MMI) waveguide configured to support at least two guided modes, and the coupling strength of at least one said optical coupler monotonically decreases with increasing wavelength throughout the operational wavelength region of the component.
2. (original) An optical branching component according to claim 1, wherein the coupling strength of each said optical coupler monotonically decreases with increasing wavelength in the operational wavelength region of the component.
3. (previously presented) An optical branching component according to claim 1, wherein each MMI waveguide is configured to support only two guided modes.
4. (previously presented) An optical branching component according to any of claim 1, wherein the optical couplers each comprise an MMI coupler.
5. (original) An optical branching component according to claim 4, wherein each of the MMI couplers has the same coupling strength.
6. (original) An optical branching component according to claim 4, wherein each of the MMI couplers has a different coupling strength.

7. (original) An optical branching component according to claim 4, wherein the phase thickness of each said MMI coupler is between  $90^\circ$  and  $180^\circ$ .

8. (original) An optical branching component according to claim 4, wherein the phase thickness of each said MMI coupler is between  $90^\circ$  and  $135^\circ$  and the phase delay,  $2\theta$ , between the two waveguides, between said two directional couplers, is defined by  $90^\circ < \theta < 180^\circ$ .

9. (original) An optical branching component according to claim 4, wherein the phase thickness of each of said two MMI couplers is between  $135^\circ$  and  $180^\circ$  and the phase delay,  $2\theta$ , between the two waveguides, between said two MMI couplers, is defined by  $0^\circ < \theta < 90^\circ$ .

10. (previously presented) An optical branching component according to claim 1, wherein said effective optical path length difference is less than the shortest operating wavelength of the component.

11. (previously presented) An optical branching component according to claim 4, wherein the geometry of each MMI coupler is optimized to result; in a minimum integrated RBE ( $RBE_{\text{average}}$ ) of the coupler.

12. (previously presented) An optical branching component according to claim 4, wherein the magnitude of the integrated RBE ( $RBE_{\text{average}}$ ) of each of said two MMI couplers is less than 1%.

13. (previously presented) An optical branching component according to claim 4, wherein the magnitude of the integrated RBE ( $RBE_{\text{average}}$ ) of each of said two MMI couplers is no greater than 0.5%.

14. (previously presented) An optical branching component according to claim 1, wherein the component is a tap device having a tap ratio of no greater than 4%.

15. (previously presented) An optical branching component according to claim 1, wherein the component is a tap device in which the variation in the tap ratio with wavelength is less than 0.1% over the operating wavelength region of the component.

16. (previously presented) An optical branching component according to claim 1, wherein each said optical coupler comprises two optical waveguides which bend away from one another along at least a portion of their lengths and which are coupled together along at least a portion of their lengths by a respective said MMI waveguide, and which are in proximity with one another in at least one region adjacent said respective MMI waveguide in which region the waveguides are substantially straight.

17. (previously presented) An optical branching component according to claim 16, further including a heater disposed on at least one said waveguide.

18. (previously presented) An optical switching device comprising two optical branching components according to claim 1, further including at least one heater.

19-24. (canceled)

25. (previously presented) An optical branching component according to claim 1, wherein the effective optical path length difference between the two waveguides is less than the shortest wavelength of the operating wavelength region.

26. (previously presented) An optical branching component according to claim 1, wherein the effective optical path length difference between the two waveguides is less than 1520nm.